

**PKZ MOTOR PROTECTION CIRCUIT
BREAKER**

278480



Overview



Specifications



Resources

How to buy




Photo is representative




Photo is representative

278480

Eaton Moeller® series PKZM01 Motor-protective
1.1 kW, I_r= 1 - 1.6 A, IP20 PKZM01-1,6

How to buy



Learn about our Push-in terminals



Configure Motor Start Combination




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

082882

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, 1 NC, Can be fitted to the front, Screw terminals

072896

Eaton Moeller® series NHI Standard auxiliary contact, 1 N/O, 1 NC, Can be retrofitted on the right side of motor-protective circuit-breakers, Screw terminals

032720

Eaton Moeller® series PKZ Extension terminal, 3p, 25mm² BK25/3-PKZ0

072894

Eaton Moeller® series NHI Standard auxiliary contact, 2N/O+1N/C, screw connection

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME Eaton Moeller® series PKZM01 Motor-protective c**CATALOG NUMBER** 278480

Product specifications

>

MODEL CODE PKZM01-1,6**EAN** 4015082784805**PRODUCT LENGTH/DEPTH** 93 mm**PRODUCT HEIGHT** 90 mm**PRODUCT WIDTH** 45 mm**PRODUCT WEIGHT** 0.292 kg

CERTIFICATIONS

CE
CSA Class No.: 3211-05
UL Category Control No.: NLRV
VDE 0660
CSA
UL
UL 60947-4-1
CSA-C22.2 No. 60947-4-1-14
UL File No.: E36332
CSA File No.: 165628
IEC/EN 60947-4-1
IEC/EN 60947

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 1.6 A**TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)** 2 x (1 - 6) mm², ferrule to DIN 46228
1 x (1 - 6) mm², ferrule to DIN 46228**10.11 SHORT-CIRCUIT RATING** Is the panel builder's responsibility. The specification must be observed.**AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN** 25 °C**RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ** 0.55 kW**10.4 CLEARANCES AND CREEPAGE DISTANCES** Meets the product standard's requirements.**10.12 ELECTROMAGNETIC COMPATIBILITY** Is the panel builder's responsibility. The specification must be observed.**10.5 MOUNTING**

10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
SWITCHING CAPACITY	1.6 A (3 contacts in series), DC-5 up to 250V 1.6 A, AC-3 up to 440 V
STRIPPING LENGTH (MAIN CABLE)	10 mm
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 400 V AC	50 kA
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
ADJUSTMENT RANGE UNDELAYED SHORT-CIRCUIT RELEASE - MAX	25 A
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE	0.75 HP
PROTECTION	Finger and back-of-hand proof Protection against di actuated from front (EN 50274)
ACTUATOR TYPE	Push button
RATED OPERATIONAL POWER AT AC-3, 440 V, 50 HZ	0.55 kW
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
RATED OPERATIONAL POWER AT AC-3, 220/230 V, 50 HZ	0.25 kW
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
DEVICE CONSTRUCTION	Built-in device fixed built-in technique
FEATURES	Phase-failure sensitivity (according to IEC/EN 6094 Part 102)
LIFESPAN, ELECTRICAL	50,000 operations (at 400V, AC-3)
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
NUMBER OF POLES	Three-pole
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to

MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with height.
RATED UNINTERRUPTED CURRENT (IU)	1.6 A
TRIPPING CHARACTERISTIC	Overload trigger: tripping class 10 A
SHORT-CIRCUIT RELEASE	24.8 A, I _{rn} , Setting range max. Basic device fixed 15.5 x I _u , Trip Blocks ± 20% tolerance, Trip blocks
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.79 W
OPERATING FREQUENCY	25 Operations/h
PRODUCT CATEGORY	Motor protective circuit breaker
SHORT-CIRCUIT CURRENT RATING (GROUP PROTECTION)	600 A, 600 V High Fault, max. Fuse, SCCR (UL/CSA) 50 kA, 600 V High Fault, Fuse, SCCR (UL/CSA) 600 A, 600 V High Fault, max. CB, SCCR (UL/CSA) 50 kA, 600 V High Fault, CB, SCCR (UL/CSA)
OVERLOAD RELEASE CURRENT SETTING - MIN	1 A
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	5.36 W
HEAT DISSIPATION CAPACITY PDISS	0 W
RATED OPERATIONAL CURRENT (IE)	1.6 A
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	0.75 HP
SUITABLE FOR	Also motors with efficiency class IE3 Branch circuit: Manual type E if used with terminal installations, (UL/CSA)
INTERNAL RESISTANCE	700 mΩ
TEMPERATURE COMPENSATION	-25 - 55 °C, Operating range ≤ 0.25 %/K, residual error for T > 40° -5 - 40 °C to IEC/EN 60947, VDE 0660
TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm ² 2 x (1 - 6) mm ²
RATED FREQUENCY - MIN	50 Hz
SHORT-CIRCUIT CURRENT	60 kA DC, up to 250 V DC, Main conducting path
POWER LOSS	5.36 W

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
LIFESPAN, MECHANICAL	50,000 Operations (Main conducting paths)
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
OVERLOAD RELEASE CURRENT SETTING - MAX	1.6 A
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	Terminals: IP00 IP20
RATED FREQUENCY - MAX	60 Hz
SWITCH OFF TECHNIQUE	Thermomagnetic
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
ADJUSTMENT RANGE UNDELAYED SHORT-CIRCUIT RELEASE - MIN	25 A
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
CONNECTION	Screw terminals
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device
FUNCTIONS	Phase failure sensitive Motor protection
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE	0.1 HP
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27 shock 10 ms
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
ALTITUDE	Max. 2000 m

Brochures

Catalogs

Characteristic curve

Declarations of conformity

Drawings

eCAD model

Installation instructions

Installation videos

Manuals and user guides

mCAD model

278480



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

