

[United States](#) [Select your location](#)

[Sign in](#)

We make what matters work*

[Products](#) [Digital Services](#) [Markets](#) [Support](#) [Company](#)

Search

[Products](#)

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)

- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)

- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)

- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

[Digital](#)

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

[Services](#)

Close Search

[Markets](#)

Close Search

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)

- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)

- [Vehicles](#)

[Support](#)

Close Search

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

[Company](#)

Close Search

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)

- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)

- [Selling to Eaton](#)

[MyEaton](#)

Close Search

Quick links



MSC motor starters combinations
283164

[Overview](#) [Specifications](#) [Resources](#)

How to buy

[Back to search](#)

[Download](#) [Zoom](#)

Photo is representative

[Download](#) [Zoom](#)

Photo is representative

[Download](#) [Zoom](#)





Photo is representative

[Download](#) [Zoom](#)

Photo is representative

[Previous](#) [Next](#)

[Download](#) [Zoom](#)

- 
- 
- 
- 

[Previous](#) [Next](#)

283164

Eaton Moeller® series MSC-D DOL starter, 380 V 400 V 415 V: 2.2 kW, Ir= 4 - 6.3 A, 24 V DC, DC voltage MSC-D-6,3-M7(24VDC)

[Add a free sample to the cart](#) [How to buy](#)

- [Configurator Motor starter combinations](#)

×



Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

[Keep My Cart](#)

[Create a New Cart](#)

×



Item is already in the cart.

Okay

Photo is representative

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

- [118561](#)
118561
Eaton Moeller® series DIL-SWD Function element, contactor, SmartWire-DT, DIL/MSC, manual/auto
- [118560](#)
118560
Eaton Moeller® series DIL-SWD Function element, contactor, SmartWire-DT, DIL/MSC
- [101044](#)
101044
Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC
- [101043](#)
101043
Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC
- [101042](#)
101042
Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC
- [101041](#)
101041
Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

Go to Previous Item

Go to Next Item

- [118561](#)
118561
Eaton Moeller® series DIL-SWD Function element, contactor, SmartWire-DT, DIL/MSC, manual/auto
- [118560](#)
118560
Eaton Moeller® series DIL-SWD Function element, contactor, SmartWire-DT, DIL/MSC
- [101044](#)

101044

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC

- [101043](#)

101043

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC

- [101042](#)

101042

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC

- [101041](#)

101041

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

[View more](#) [View less](#)

- [General specifications](#)
- [Product specifications](#)

General specifications

Product Name

Eaton Moeller® series MSC-D DOL starter

Catalog Number

283164

Model Code

MSC-D-6,3-M7(24VDC)

EAN

4015082831646

Product Length/Depth

95 mm

Product Height

180 mm

Product Width

45 mm

Product Weight

0.645 kg

Certifications

IEC/EN 60947-4-1

CSA

CSA Class No.: 3211-24

UL

UL File No.: E36332

UL 60947-4-1

VDE 0660

CE

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

CSA File No.: 012528

Product specifications

Rated operational current for specified heat dissipation (In)

6.3 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Rated operational power at AC-3, 380/400 V, 50 Hz
2.2 kW

Rated operational voltage
230 - 415 V AC

Rated conditional short-circuit current, type 1, 480 Y/277 V
0 A

Rated control supply voltage (Us) at AC, 50 Hz - min
0 V

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting method
DIN rail

10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

Rated power at 575 V, 60 Hz, 3-phase
0 kW

Rated power at 460 V, 60 Hz, 3-phase
0 kW

10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

Rated control supply voltage (Us) at DC - min
24 V

Fitted with:
Short-circuit release
Number of pilot lights
0

Short-circuit current rating (high fault at 600 V)
100 kA, Fuse, SCCR (UL/CSA)
30 A, Class J/CC, max. Fuse, SCCR (UL/CSA)

Rated control supply voltage (Us) at AC, 50 Hz - max
0 V

Coordination type
2

10.8 Connections for external conductors
Is the panel builder's responsibility.

Coordination class (IEC 60947-4-3)
Class 2

Rated conditional short-circuit current, type 1, 600 Y/347 V
0 A

Ambient operating temperature - max
55 °C

Rated operational power at AC-3, 220/230 V, 50 Hz
1.5 kW

Connection to SmartWire-DT
No

Number of command positions
0

Static heat dissipation, non-current-dependent Pvs
2.6 W

Electrical connection type of main circuit
Screw connection

Electrical connection type for auxiliary- and control-current circuit
Screw connection

Power consumption (sealing) at DC
2.6 W

Rated control supply voltage (Us) at DC - max
24 V

10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

Ambient operating temperature - min
-25 °C

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Class

CLASS 10

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Heat dissipation per pole, current-dependent P_{vid}

2.2 W

Actuating voltage

24 VDC

Voltage type

DC

Switching capacity (auxiliary contacts, general use)

1 A, 250 VDC, (UL/CSA)

15 A, 600 VAC, (UL/CSA)

Overload release current setting - min

4 A

Equipment heat dissipation, current-dependent P_{vid}

6.6 W

Heat dissipation capacity P_{diss}

0 W

Rated operational current (I_e)

5 A

Suitable for

Also motors with efficiency class IE3

Number of auxiliary contacts (normally closed contacts)

0

Rated conditional short-circuit current (I_q), type 2, 380 V, 400 V, 415 V

50000 A

Power consumption

2.6 W

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Overload release current setting - max

6.3 A

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Overvoltage category

III

Degree of protection

IP20

NEMA Other

Pollution degree

3

Rated control supply voltage (U_s) at AC, 60 Hz - min

0 V

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Rated impulse withstand voltage (U_{imp})

6000 VAC

Connection

Screw terminals

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Functions

Temperature compensated overload protection

Rated conditional short-circuit current (I_q), type 2, 230 V

50000 A

Type

Starter with Bi-Metal release

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

Short-circuit release (I_{rm}) - max

97.7 A

Rated control supply voltage (U_s) at AC, 60 Hz - max

0 V

Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V

6.3 A

Model

Direct starter

Number of auxiliary contacts (normally open contacts)

1

Altitude


Max. 2000 m

Switching capacity (auxiliary contacts, pilot duty)

P300, DC operated (UL/CSA)

A600, AC operated (UL/CSA)

Serial Number Verified :

Authenticated: 

The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

Brochures

- [Motor Starters in System xStart - brochure](#)
- [Save time and space thanks to the new link module PKZM0-XDM32ME](#)
- [Simple, flexible and safe! Distribution system for motor-starter combinations](#)

Download all files

Catalogs

- [Product Range Catalog Switching and protecting motors](#)

Declarations of conformity

- [DA-DC-00004878.pdf](#)
- [DA-DC-00004910.pdf](#)

Drawings

- [eaton-manual-motor-starters-motorstarter-msc-d-dol-starter-dimensions.eps](#)
- [eaton-manual-motor-starters-mounting-msc-d-dol-starter-3d-drawing.eps](#)
- [eaton-general-ie-ready-dilm-contactor-standards.eps](#)

Download all files

eCAD model

- [ETN.MSC-D-6.3-M7\(24VDC\).edz](#)

Installation instructions

- [IL034014ZU](#)
- [IL034038ZU](#)

Download all files

Installation videos

- [WIN-WIN with push-in technology](#)

mCAD model

- [DA-CD-msc_d_bg1](#)
- [DA-CS-msc_d_bg1](#)

Download all files

Wiring diagrams

- [eaton-manual-motor-starters-device-msc-d-dol-starter-wiring-diagram.eps](#)

Export product specification

-

x



Enter your city, state, or zip code or [Locate me](#)

City, state

Search

Show locations that offer:

- Product pickup
- Order online and ship product

- 283164

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)
- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

-
-
-
-

[View all social media](#)

- [sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

Back to top of the page

Are you sure?

Cancel Sign out

Are you sure?

Cancel Sign out

×

×