



283176
MSC-R-1,6-M7(230V50HZ)

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM7.0

Approvals

Dimensions

DELIVERY PROGRAM

Basic function
Reversing starters (complete devices)

Basic device
MSC



Notes
Also suitable for motors with efficiency class IE3.

Connection technique
Screw terminals

Connection to SmartWire-DT
no


Motor ratings

Motor rating [P]
AC-3
380 V 400 V 415 V [P]
0.37
0.55 kW

Rated operational current
AC-3
380 V 400 V 415 V [I_e]
1.1
1.5 A


Rated short-circuit current 380 - 415 V [I_k]
150 kA

Setting range

Setting range of overload releases  [I_n]
1 - 1.6 A

Coordination
Type of coordination "1"
Type of coordination "2"

Contact sequence



Actuating voltage
230 V 50 Hz, 240 V 60 Hz

AC voltage

Motor-protective circuit-breakers

PKZM0-1,6
PKZM0-1,6 Type

Contactors

DILM7-01(...) Part no.

DOL starter wiring set

Mechanical connection element and electrical
electric contact module

Notes

The reversing starter (complete unit) consists of a FKZMD motor-protective circuit-breaker and two DILM contactors.

With the adapter-less top-hat rail mounting of starters up to 12 A, only the motor-protective circuit-breaker on the top-hat rail requires an adapter. The contactors are provided with mechanical support via a mechanical connection element.

Control wire guide with max. 6 conductors up to 2.5mm external diameter or 4 conductors up to 3.5mm external diameter.

From 16 A, the motor-protective circuit-breakers and contactors are mounted on the top-hat rail adapter plate.

The connection of the main circuit between FKZ and contactor is established with electrical contact modules.

Complete units with mechanical interlock, starters up to 12 A also feature electrical interlock.

When using the auxiliary contacts DILA-XHIT... (□ 101042) the plug-in electrical connector can be removed without the removal of the front mounting auxiliary contact.

For further information	Page
Technical data FKZMD	□ FKZMD
Accessories FKZ	□ 072896
Technical data DILM	□ DILM
Further actuating voltages	□ 276537
DILM accessories	□ 281199

TECHNICAL DATA**General**

Standards

UL 508 (on request)
CSA C22.2 No. 14 (on request)

Mounting position



Altitude
Max. 2000 m

Ambient temperature
-25 - +55

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
6000 V AC

Overvoltage category/pollution degree
III/3

Rated operational voltage [U_e]
230 - 415 V

Rated operational current
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
1.6 A

Additional technical data

Motor protective circuit breaker PKZMD, PKE
PKZMD motor-protective circuit-breakers, see
motor-protective circuit-breakers/PKZMD product
group
DILM contactors, see contactor product group
DILET timing relay, ETR, see contactors, electronic
timing relays product group

DILM contactors
Power consumption of the coil in a cold state and
 $1.0 \times U_s$
Dual-voltage coil 50 Hz [Sealing]
1.2 W

Rating data for approved types

Auxiliary contacts

Flot Duty
AC operated
A600

Auxiliary contacts
Flot Duty
DC operated
P300

Auxiliary contacts
General Use
AC
600 V

Auxiliary contacts
General Use
AC
15 A

Auxiliary contacts
General Use
DC
250 V

Auxiliary contacts
General Use
DC
1 A

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
1.6 A

Heat dissipation per pole, current-dependent [P_{id}]
1.9 W

Equipment heat dissipation, current-dependent
[P_{id}]
5.7 W

Static heat dissipation, non-current-dependent [P_{vs}]
1.4 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+55 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Mtor starter/Mtor starter combination (EC001037)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Mtor starter combination (ecl@ss10.0.1-27-37-09-05 [AJZ718013])

Kind of motor starter
Reversing starter

With short-circuit release
Yes

Rated control supply voltage U_s at AC 50HZ
230 - 230 V

Rated control supply voltage U_s at AC 60HZ
0 - 0 V

Rated control supply voltage U_s at DC
0 - 0 V

Voltage type for actuating
AC

Rated operation power at AC-3, 230 V, 3-phase
0.25 kW

Rated operation power at AC-3, 400 V
0.55 kW

Rated power, 460 V, 60 Hz, 3-phase

0 kW

Rated power, 575 V, 60 Hz, 3-phase
0 kW

Rated operation current I_e
1.5 A

Rated operation current at AC-3, 400 V
1.6 A

Overload release current setting
1.6 - 1.6 A

Rated conditional short-circuit current, type 1, 480
Y/277 V
0 A

Rated conditional short-circuit current, type 1, 600
Y/347 V
0 A

Rated conditional short-circuit current, type 2, 230
V
50 A

Rated conditional short-circuit current, type 2, 400
V
50 A

Number of auxiliary contacts as normally open
contact
0

Number of auxiliary contacts as normally closed
contact
0

Ambient temperature, upper operating limit
60 °C

Temperature compensated overload protection
Yes

Release class
CLASS 10 A

Type of electrical connection of main circuit
Screw connection

Type of electrical connection for auxiliary- and
control current circuit
Screw connection

Rail mounting possible
Yes

With transformer
No

Number of command positions
0

Suitable for emergency stop
No

Coordination class according to IEC 60947-4-3
Class 2

Number of indicator lights
0

External reset possible
No

With fuse
No

Degree of protection (IP)
IP20

Degree of protection (NEMA)
Other

Supporting protocol for TCP/IP
No

Supporting protocol for PROFIBUS
No

Supporting protocol for CAN
No

Supporting protocol for INTERBUS
No

Supporting protocol for ASI
No

Supporting protocol for MODBUS
No

Supporting protocol for Data-Highway
No

Supporting protocol for DeviceNet
No

Supporting protocol for SUCONET
No

Supporting protocol for LON
No

Supporting protocol for PROFINET IO
No

Supporting protocol for PROFINET CBA
No

Supporting protocol for SERCOS
No

Supporting protocol for Foundation Fieldbus
No

Supporting protocol for EtherNet/IP
No

Supporting protocol for AS-Interface Safety at
Work
No

Supporting protocol for DeviceNet Safety
No

Supporting protocol for INTERBUS-Safety
No

Supporting protocol for PROFI-safe
No

Supporting protocol for SafetyBUS p
No

Supporting protocol for other bus systems
No

Width
90 mm

Height
180 mm

Depth
95 mm

APPROVALS

Product Standards
UL60947-4-1A; CSA-C22.2 No. 14-10; IEC60947-4-1; CE marking

UL File No.
E123500

UL Category Control No.
NKJH


CSA File No.
12528

CSA Class No.
3211-24

North America Certification
UL listed, CSA certified

Specially designed for North America
No

DIMENSIONS



MSC-R...-M7[...12]...



