

DIGITAL NZM MOLDED CASE CIRCUIT BREAKER

286006



Overview




Specifications



Resources

Technical



286006

Eaton Moeller series NZM - Molded Case Circuit Breaker transformer

[Contact me about this product](#)

GENERAL SPECIFICATIONS

General specifications >

PRODUCT NAME Eaton Moeller series NZM release

CATALOG NUMBER 286006

Product specifications >

MODEL CODE PFR-WC

EAN 4015082860066

PRODUCT LENGTH/DEPTH 57 mm

PRODUCT HEIGHT 135 mm

PRODUCT WIDTH 10 mm

PRODUCT WEIGHT 0.009 kg

COMPLIANCES RoHS conform

CERTIFICATIONS IEC

PRODUCT SPECIFICATIONS

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications must be observed.
FRAME	NZM1/2/3/4
POWER ON-DELAY TIME - MIN	0 ms
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	0 V
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications must be observed.
MOUNTING METHOD	DIN top-hat rail mounting
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
RATED FAULT CURRENT - MAX	0 A
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	0 V
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
SPECIAL FEATURES	For the DIN rail mounting of the PFR-W... current sizes
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	0 V
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
POWER ON-DELAY TIME - MAX	0 ms
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise. Eaton will provide heat dissipation data for the device.
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
TYPE	Accessory Earth-fault releases, transformer Voltage releases
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	0 V
RATED OPERATING VOLTAGE (UE) - MAX	0 V
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
RATED FAULT CURRENT - MIN	0 A
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to

Brochures

Catalogs

Certification reports

Drawings

Installation instructions

Installation videos

Technical data sheets



Technical support

286006



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.