DATASHEET - IZMX-CAS403-3200-1



Cassette 3200A, IZMX403 without control cable connection



Part no.IZMX-CAS403-3200-1Catalog No.183949Alternate Catalog67C2752A51No.EL-NummerKorway)4398358

Delivery program

Product range			Accessories
Accessories			Withdrawable units
Accessories			Cassettes
			Equipment supplied: arcing chamber cover
Rated current	In	Α	3200
Pole			3
For use with			IZMX403W INX403W
Instructions			Without terminal blocks for the control circuit terminals. Please order the required quantity separately.
Information about equipment supplied			with arcing chamber cover
Installation type			Withdrawable

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)					
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss10.0.1-27-37-04-22 [ACN955011])					
Rated current In	А	3200			
Number of poles		3			
Version as busbar adapter		No			
Version as built-in device		Yes			
Type of electrical connection of main circuit		Rail connection			

Dimensions

