DATASHEET - IZMX-RP-PXR-1



Programmable Rating Plug

Part no. IZMX-RP-PXR-1 Catalog No. 183992

EL-Nummer (Norway)

4398401



Delivery program

Product range	Accessories
Accessories	Options / accessories trip blocks
Accessories	Programmable rating plug (rate current module)
	Rated operational current In can be programmed to be lower, e.g., in order to adapt to a change in conditions in the relevant application. The value can only be changed to a value less than or equal to the basic device's rated operational current lu. A USB drive with a passcode and 17 plugs for changing the inscription indicating the new In rated operational current are provided.
Suitable for circuit-breaker lu=	200 A 4000A aber ≤ lu
For use with	IZMX16 IZMX40 IEC

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

technology (accessories) (eci-ssite.e.i 27 of to 32 [Akkorooto])		
Type of accessory	Other	