



Signalling switch ready to switch-on, 1W

Part no. IZMX-LCS-1
Catalog No. 184104
Alternate Catalog No. 67C2814G33
EL-Nummer (Norway) 4398467

Delivery program

Product range		Accessories
Accessories		Auxiliary contact
Accessories		Operational readiness indicator
		1 changeover contact
For use with		IZMX16..., IZMX40... INX16..., INX40...
Instructions		For signaling availability. Alternatively, also for automatic closing upon availability. The retrofit kit includes the required SEC control cable terminals.
		OFF message

Technical data

Rated breaking capacity

Inductive load		
250 V AC	A	10
125 V DC	A	0.5
250 V DC	A	0.25

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss10.0.1-27-37-13-02 [AKN342013])		
Number of contacts as change-over contact		1
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of fault-signal switches		
Rated operation current Ie at AC-15, 230 V	A	10
Type of electric connection		Flat plug-in connection
Model		Integrable
Mounting method		Other
Lamp holder		