

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



ZMX-LCS-SR-1 - Signalling switch ready to switch on, 1W (ZMX-SR)



184106 ZMX-LCS-SR-1

[Overview](#) [Specifications](#) [Resources](#)



## 184106 ZMX-LCS-SR-1

Signalling switch ready to switch on, 1W (ZMX-SR)

Alternate Catalog No.

67C2814G31

EL-Nummer (Norway)

4398469

Accessories, Operational readiness indicator with plug for direction connection to spring release, Automatic closing after readiness for operation., Can only be used together with a closing release, For use with ZMX16..., ZMX40..., INX16..., INX40..., 1 changeover contact

- [Delivery program](#)
- [Technical data](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)

### Delivery program

Product range

Accessories

Accessories

Auxiliary contact

Accessories

Operational readiness indicator with plug for direction connection to spring release

Automatic closing after readiness for operation.

Can only be used together with a closing release

For use with

ZMX16..., ZMX40...

INX16..., INX40...

#### Instructions

Can be used with ZMX16(40)-SR... closing release for automatic closing upon availability

1 changeover contact

### Technical data

Rated breaking capacity

Inductive load250 V AC

10 A

Inductive load125 V DC

0.5 A

Inductive load250 V DC

0.25 A

### Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)  
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss10.0.1-27-37-13-02 [AKN342013])  
Number of contacts as change-over contact  
1  
Number of contacts as normally open contact  
0  
Number of contacts as normally closed contact  
0  
Number of fault-signal switches  
Rated operation current  $I_e$  at AC-15, 230 V  
10 A  
Type of electric connection  
Flat plug-in connection  
Model  
Integrable  
Mounting method  
Other  
Lamp holder

## Product photo



1230PIC-1243

Photo

## 3D drawing



1230DRV-1040

Line drawing

## CAD data


### edz files

- [DA-CE-ETN.IZMX-LCS-SR-1](#)  
File  
(Web)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH