



Signalling switch tripped, 2W

Part no. IZMX-OTS16-1
Catalog No. 184117
Alternate Catalog No. 67C2824G42
EL-Nummer (Norway) 4398480

Delivery program

Product range		Accessories
Accessories		Trip indication / Reset options
Accessories		Trip-indicating auxiliary switch
		"Triggered" signaling contact with two changeover contacts
For use with		IZMX16...
Instructions		The retrofit kit includes the required SEC control cable terminals.

Technical data

Rated breaking capacity

Inductive load			
250 V AC		A	10
125 V DC		A	0.5
250 V DC		A	0.25

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecI@ss10.0.1-27-37-13-02 [AKN342013])			
Number of contacts as change-over contact			2
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of fault-signal switches			
Rated operation current I _e at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection
Model			Integrable
Mounting method			Other
Lamp holder			