



**Connections, front, 2500A, IZMX40, 3 p, withdrawable**

**Part no.** IZMX-TF403-2500W-1  
**Catalog No.** 184178  
**Alternate Catalog No.** 67C2975H03  
**EL-Nummer (Norway)** 4398521

**Delivery program**

|                                      |       |   |   |
|--------------------------------------|-------|---|---|
| Product range                        |       |   | Accessories   |
| Accessories                          |       |   | Main terminal kits  |
| Accessories                          |       |   | Front connections   |
|                                      |       |   | This connection kit comes with front terminals for connection to the cassette. The circuit-breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit-breaker is installed in the enclosure. This way, the final connection to the circuit-breaker can be made from the front. |
| Rated current                        | $I_n$ | A | 2000, 2500  |
| Pole                                 |       |   | 3   |
| For use with                         |       |   | IZMX40...3...20W<br>IZMX40...3...25W<br>INX40...3...20W<br>INX40...3...25W  |
| Information about equipment supplied |       |   | Each set includes the connections for top and bottom. 3-pole for 6 connections, 4-pole for 8 connections<br>Screws, washers, and supports are included as standard.   |
| Installation type                    |       |   | Withdrawable  |

**Design verification as per IEC/EN 61439**

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 70  |

**Technical data ETIM 7.0**

|   |  |  |   |
|---|--|--|---|
| Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)  |  |  |   |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ec@ss10.0.1-27-37-13-05 [ACN990012]) |  |  |   |
| Suitable for number of poles  |  |  | 3 |

## Dimensions

