



Connections, front, 3200A, IZMX40, 4 p, fixed mounted design

Part no. IZMX-TF404-3200F-1
Catalog No. 184182
Alternate Catalog No. 67C2975H04
EL-Nummer (Norway) 4398525

Delivery program

| | | | |
|--------------------------------------|-------|---|--|
| Product range | | | Accessories |
| Accessories | | | Main terminal kits |
| Accessories | | | Front connections |
| | | | This connection kit comes with front terminals for connection to the circuit-breaker. The circuit-breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit-breaker is installed in the enclosure. This way, the final connection to the circuit-breaker can be made from the front. |
| Rated current | I_n | A | 3200 |
| Pole | | | 4 |
| For use with | | | IZMX40...4...32F INX40...4...32F |
| Information about equipment supplied | | | Each set includes the connections for top and bottom. 3-pole for 6 connections, 4-pole for 8 connections Screws, washers, and supports are included as standard. |
| Installation type | | | Fixed |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |

Technical data ETIM 7.0

| | | | |
|--|--|--|---|
| Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecI@ss10.0.1-27-37-13-05 [ACN990012]) | | | |
| Suitable for number of poles | | | 4 |

Dimensions

