



Signalling switch, circuit-breaker position, 1W, right or left

Part no. IZMX-CS40-1
Catalog No. 184196
Alternate Catalog No. 65A2788G31
EL-Nummer (Norway) 4398539

Delivery program

Product range			Accessories
Accessories			Withdrawable units
Accessories			Position signalling switches
			One changeover contact each for the Disconnected, Test, and Connected positions. for fitting to left or right
For use with			IZMX-CAS40...
Instructions			The retrofit kit includes the required SEC control cable terminals.
Installation type			Withdrawable

Technical data

Rated breaking capacity

Inductive load			
250 V AC		A	10
125 V DC		A	0.5
250 V DC		A	0.25

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ec@ss10.0.1-27-37-13-02 [AKN342013])			
Number of contacts as change-over contact			1
Number of contacts as normally open contact			2
Number of contacts as normally closed contact			2
Number of fault-signal switches			
Rated operation current I _e at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection
Model			Integrable
Mounting method			Floor fastening
Lamp holder			