



Interlock, cassette, +door



Powering Business Worldwide™

Part no. IZMX-DI40-W-1
Catalog No. 184205
Alternate Catalog No. 65A3002G01
EL-Nummer (Norway) 4398548

Delivery program

Product range			Accessories
Accessories			Interlocks
Accessories			door interlock
			Door interlock mounting kit The door interlock is installed on the cassette and keeps the enclosure doors closed in the "CONNECTED" and "TEST" positions. It will not be possible to open the enclosure door until the circuit-breaker in the cassette is in the safe "Disconnected" position. In case of emergency, the interlock can be released with a screwdriver.
For use with			IZMX40...W INX40...W
Installation type			Withdrawable

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecl@ss10.0.1-27-37-13-03 [AKN341013])			
Auxiliary contacts, extendable			No
Number of contacts as normally closed contact			0
Number of contacts as normally open contact			0