DATASHEET - IZMX-MIL2C-F16-1



Mechanical interlock, TYPE 2, bowden cables, F

65A2840G33

Powering Business Worldwide*

Part no. IZMX-MIL2C-F16-1 Catalog No. 184206

Alternate Catalog

No.

EL-Nummer 4398549

(Norway)

Delivery program

Product range	Accessories
Accessories	Interlocks
Accessories	Mechanical interlock, fixed mounting
	Туре 2
	For 2 circuit-breakers with the same or different frame size: interlock: A against B. In addition, an IZMX-MIL-CAB cable kit with the desired length is required. Select the appropriate part no. for each circuit-breaker.
For use with	IZMX16 INX16
Installation type	Fixed

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecl@ss10.0.1-27-37-13-03 [AKN341013])

Auxiliary contacts, extendable	No
Number of contacts as normally closed contact	0
Number of contacts as normally open contact	0

Dimensions

