

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



ZMX-ML3133C-F40-1 - Mechanical interlock, TYPE 31, bow den cables, F



184210 ZMX-ML3133C-F40-1

[Overview](#) [Specifications](#) [Resources](#)



184210 ZMX-MIL3133C-F40-1

Mechanical interlock, TYPE 31, bow den cables, F

Alternate Catalog No.

65A2840G44

EL-Nummer (Norway)

4398553

Accessories, Mechanical interlock, fixed mounting, Type 33, For 3 circuit-breakers with the same or different frame size: interlock: A, C against B. When B is off, A and C can be switched on. B can be switched on only when A and C are OFF. In addition, two ZMX-ML-CAB... cable kits with the desired length are required. Select the appropriate part no. for each circuit-breaker., Installation type Fixed, For use with ZMX40..., INX40...

- [Delivery program](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Dimensions](#)

Delivery program

Product range

Accessories

Accessories

Interlocks

Accessories

Mechanical interlock, fixed mounting

Type 33

For 3 circuit-breakers with the same or different frame size: interlock: A, C against B. When B is off, A and C can be switched on. B can be switched on only when A and C are OFF. In addition, two ZMX-ML-CAB... cable kits with the desired length are required. Select the appropriate part no. for each circuit-breaker.

For use with

ZMX40...

INX40...

Installation type

Fixed

Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecl@ss10.0.1-27-37-13-03 [AKN341013])


Auxiliary contacts, extendable

No

Number of contacts as normally closed contact

0
Number of contacts as normally open contact
0

Dimensions



CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-izmx_mil_f40](#)
File
(Web)

edz files

- [DA-CE-ETN.IZMX-ML3133C-F40-1](#)
File
(Web)


Step files

- [DA-CS-izmx_mil_f40](#)
File
(Web)


Product photo

- 
[1230PIC-1265](#)
Photo

3D drawing

- 
[1230DRV-1070](#)
Line drawing

Dimensions single product

- 
[1230DIM-401](#)
Line drawing

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

