# DATASHEET - IZMX-MIL32C-F40-1



Interlock, mechanical, type 32, Bowden cable, fixed



Part no.IZMX-MIL32C-F40-1Catalog No.184211Alternate Catalog65A2840G45No.EL-Nummer4398554(Norway)

#### **Delivery program**

Product range	Accessories
Accessories	Interlocks
Accessories	Mechanical interlock, fixed mounting
	Туре 32
	For 3 circuit-breakers with the same or different frame size: interlock: 2 against 1 / max. 2 ON. Any one or two circuit-breakers can be closed at the same time. In addition, three IZMX-MIL-CAB cable kits are required. Select the appropriate part no. for each circuit-breaker.
For use with	IZMX40 INX40
Installation type	Fixed

### **Design verification as per IEC/EN 61439**

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

#### **Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)

Electric engineering, automation, process control engineering / Low-voltage switc (ecl@ss10.0.1-27-37-13-03 [AKN341013])	h technology / Component for low-voltage switching technology / Mechanic interlock for switch
Auxiliary contacts, extendable	No
Number of contacts as normally closed contact	0
Number of contacts as normally open contact	0

## **Dimensions**

