



Mechanical interlock, TYPE 2, 31, 33, bowden cables, W

Part no. IZMX-MIL3133C-W16-1
Catalog No. 184213
Alternate Catalog No. 65A2840G31
EL-Nummer (Norway) 4398556

Delivery program

| | | |
|-------------------|--|--|
| Product range | | Accessories |
| Accessories | | Withdrawable units |
| Accessories | | Mechanical interlock |
| | | Type 31 + 33 |
| | | for 3 circuit-breakers: Three incoming units (A, B, C), normal or emergency network. Only one of the three switches can be switched on at any one time. Three cable kits are required in addition. |
| For use with | | IZMX16...W INX16...W |
| Installation type | | Withdrawable |

Design verification as per IEC/EN 61439

| | | |
|--|----|-----|
| Technical data for design verification | | |
| Operating ambient temperature min. | °C | -25 |
| Operating ambient temperature max. | °C | 70 |

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecI@ss10.0.1-27-37-13-03 [AKN341013])

| | | |
|---|--|----|
| Auxiliary contacts, extendable | | No |
| Number of contacts as normally closed contact | | 0 |
| Number of contacts as normally open contact | | 0 |

Dimensions



