



**Motor operator 110-125 VAC/DC**

**Part no.** IZMX-M40-110AD-1  
**Catalog No.** 184262  
**Alternate Catalog No.** 68D2905G51  
**EL-Nummer (Norway)** 4398605

**Delivery program**

Product range			Accessories
Accessories			Remote switching
Accessories			Motor operator
			The motor automatically tensions the spring force storage mechanism for remote or local actuation. Retrofitting kit
Maximum operating frequency	Actuations/minute		3
			Please note - the circuit-breaker's switching frequency = 60/h
Rated control voltage	$U_s$	V	110 - 127 V AC 50/60 Hz 110 - 125 V DC
Operating range	$x U_s$	Factor	0,85 - 1,1
For use with			IZMX40... INX40...
<b>Instructions</b>			The retrofit kit includes the required SEC control cable terminals.
Information about equipment supplied			A signaling switch "Spring-operated stored energy mechanism tensioned" message is included as standard.

**Technical data**

Necessary time required for charging the spring-operated stored energy mechanism at $1 \times U_s$			6 s AC 50/60 Hz 6 s DC
Rated operational current	$I_n$	A	3 A AC 50/60 Hz 2 A DC
Starting current		A	9 A AC 50/60 Hz 7.5 A DC
Power consumption			425 VA AC 50/60 Hz 275 W DC

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Motor operator for power circuit-breaker (EC001030)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Electrical drive for circuit breakers (ecl@ss10.0.1-27-37-04-12 [AKF010013])			
Type of switch drive			Motor drive
Rated control supply voltage $U_s$ at AC 50HZ		V	110 - 127
Rated control supply voltage $U_s$ at AC 60HZ		V	110 - 127
Rated control supply voltage $U_s$ at DC		V	110 - 125
Voltage type for actuating			AC/DC