

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

197225

Eaton Moeller® series EASY 3 x Bus connector plug between base unit and expansion unit/bus module and 3 x end covers, For use with easyE4

197509

Eaton Moeller® series EASY easyE4 control relay, basic unit (expandable, Ethernet), 100–240 VAC, 100–240 VDC (cULus: 100–110 VDC), digital inputs: 8, digital outputs: 4 relay, push-in

197214

Eaton Moeller® series EASY Control relays, easyE4 (expandable, Ethernet), 24 V DC, Inputs Digital: 8, of which can be used as analog: 4, screw terminal

197505

Eaton Moeller® series EASY Control relays, easyE4 (expandable, Ethernet), 24 V DC, 24 V AC, Inputs Digital: 8, of which can be used as analog: 4, push-in

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications	>	PRODUCT NAME	Eaton Moeller® series EASY I/O expansion
		CATALOG NUMBER	197223
Product specifications	>	MODEL CODE	EASY-E4-DC-6AE1
		EAN	4015080892847
		PRODUCT LENGTH/DEPTH	58 mm
		PRODUCT HEIGHT	90 mm
		PRODUCT WIDTH	36 mm
		PRODUCT WEIGHT	0.1 kg
		CERTIFICATIONS	CSA-C22.2 No. 61010 IEC/EN 61000-4-2 EN 61010 IEC/EN 61131-2 IEC/EN 61000-6-2 EN 50178 IEC/EN 61000-6-3 CULus per UL 61010 IEC 60068-2-27 IEC 60068-2-30 IEC 60068-2-6 UL Listed UL Category Control No.: NRAQ, NRAQ7 UL File No.: E205091 DNV GL CE UL hazardous location class I UL hazardous location division 2 UL hazardous location group A (acetylene) UL hazardous location group B (hydrogen) UL hazardous location group C (ethylene) UL hazardous location group D (propane)

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
RATED OPERATIONAL VOLTAGE	20.4 - 28.8 V DC 24 V DC (-15 %/+ 20 % - power supply)
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
MOUNTING METHOD	Front build in possible Rail mounting possible Wall mounting/direct mounting Top-hat rail fixing (according to IEC/EN 60715, 35) Screw fixing using fixing brackets ZB4-101-GF1 (ac

AIR PRESSURE	795 - 1080 hPa (operation)
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
SURGE RATING	0.5 kV, Supply cables, symmetrical, power pulses (S) According to IEC/EN 61000-4-5, power pulses (S) 1 kV, Supply cables, asymmetrical, power pulses (S)
VIBRATION RESISTANCE	57 - 150 Hz, 2 g constant acceleration 10 - 57 Hz, 0.15 mm constant amplitude According to IEC/EN 60068-2-6
EXPLOSION SAFETY CATEGORY FOR GAS	None
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
SWITCHING CURRENT	0 A
FEATURES	Expandable Expansion device
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
NUMBER OF HW-INTERFACES (SERIAL TTY)	0
SUPPLY VOLTAGE AT AC, 60 HZ - MAX	0 VAC
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
VOLTAGE TYPE	DC
CATEGORY (EN 954-1)	None
PRODUCT CATEGORY	Control relays easyE4
POTENTIAL ISOLATION	Between Analog inputs and Power supply: no Between Analog inputs and Inputs/Outputs: no Between Analog outputs and Inputs/Outputs: no Between Analog inputs and expansion devices: yes Between Analog outputs and Power supply: no Between Analog outputs and expansion devices: no
RADIO INTERFERENCE CLASS	Class B (EN 61000-6-3)
RESIDUAL RIPPLE	≤ 5 %
TERMINAL CAPACITY	0.2 - 2.5 mm ² (22 - 12 AWG), flexible with ferrule 0.2 - 4 mm ² (AWG 22 - 12), solid
HEAT DISSIPATION CAPACITY PDISS	0 W
NUMBER OF HW-INTERFACES (RS-422)	0
INSULATION RESISTANCE	According to EN 50178, EN 61010-2-201, UL6101 NO. 61010-2-201


OUTPUT	Current Voltage
ELECTROMAGNETIC FIELDS	3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-1) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-1) 10 V/m at 0.8 - 1.0 GHz (according to IEC EN 61000-1)
INRUSH CURRENT	12.5 A (for 6 ms)
PROTOCOL	TCP/IP MODBUS
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	IP20
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
POLLUTION DEGREE	2
SIL (IEC 61508)	None
TIGHTENING TORQUE	0.6 Nm, Screw terminals
TYPE	easyE4 extension
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
ENVIRONMENTAL CONDITIONS	Clearance in air and creepage distances according to IEC 60604-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201 Condensation: prevent with appropriate measures
PROTECTION AGAINST POLARITY REVERSAL	Yes, for supply voltage (Siemens MPI optional)
SIGNAL RANGE	4 - 20 mA, Analog outputs 0 - 20 mA, Analog inputs 0 - 10 V DC, Analog inputs 0 - 10 V DC, Analog outputs 4 - 20 mA, Analog inputs 0 - 20 mA, Analog outputs
SHOCK RESISTANCE	15 g, Mechanical, according to IEC/EN 60068-2-27 shock 11 ms, 18 Impacts
NUMBER OF INPUTS (ANALOG)	4
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted
NUMBER OF HW-INTERFACES (RS-485)	0
NUMBER OF HW-INTERFACES (INDUSTRIAL ETHERNET)	0
	Voltage

INPUT	Current
FREQUENCY RATING	6.5 Hz
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
CONTACT DISCHARGE	6 kV
SUPPLY VOLTAGE AT DC - MIN	20.4 VDC
NUMBER OF HW-INTERFACES (WIRELESS)	0
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	2.5 W
INPUT IMPEDANCE	11.2 kΩ
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
NUMBER OF HW-INTERFACES (RS-232)	0
NUMBER OF INPUTS (DIGITAL)	0
CABLE LENGTH	≤ 30 m, screened, Analog outputs ≤ 30 m, screened, Analog inputs 10 m, screened, Analog inputs
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
VOLTAGE DIPS	20 ms ≤ 10 ms, Bridging voltage dips
SUPPLY VOLTAGE AT DC - MAX	28.8 VDC
MOUNTING POSITION	Horizontal Vertical
SOFTWARE	EASYSOFT-SWLIC/easySof7
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
SAFETY PERFORMANCE LEVEL (EN ISO 13849-1)	None
RESOLUTION	<ul style="list-style-type: none"> • 12 Bit (value 0 - 4095, Analog inputs) • 12 Bit (value 0 - 4095, Analog outputs)
SHORT-CIRCUIT PROTECTION	≥ 1A (T), Fuse, Power supply
DROP AND TOPPLE	50 mm Drop height, Drop to IEC/EN 60068-2-31
SUPPLY VOLTAGE AT AC, 60 HZ - MIN	0 VAC
HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	0.3 m
EQUIPMENT HEAT DISSIPATION CURRENT	

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
NUMBER OF OUTPUTS (ANALOG)	2
AIR DISCHARGE	8 kV
NUMBER OF HW-INTERFACES (USB)	0
HEAT DISSIPATION	3.4 W (at 24 V DC)
ACCURACY	1 %, Analog inputs at -25 °C - 55 °C
NUMBER OF OUTPUTS (DIGITAL)	0
POWER CONSUMPTION	2.5 W
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
CONNECTION TYPE	Screw terminal
NUMBER OF HW-INTERFACES (OTHER)	0
RELATIVE HUMIDITY	5 - 95 % (IEC 60068-2-30, IEC 60068-2-78)
SUPPLY VOLTAGE AT AC, 50 HZ - MIN	0 VAC
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
SUPPLY VOLTAGE AT AC, 50 HZ - MAX	0 VAC
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device.
NUMBER OF HW-INTERFACES (PARALLEL)	0
EXPLOSION SAFETY CATEGORY FOR DUST	None
SCREWDRIVER SIZE	3.5 x 0.8 mm, Terminal screw
BURST IMPULSE	According to IEC/EN 61000-4-4 2 kV, Supply cable 2 kV, Signal cable
BASE TYPE	No
NUMBER OF INTERFACES (PROFINET)	0



[Download easySoft](#)



[easySoft tutorials](#)



[Sample application](#)

Brochures

Declarations of conformity

Drawings

Installation instructions

Installation videos

Manuals and user guides

mCAD model

197223



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

