



**140040**  
**XNE-16DI-24VDC-P**

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Dimensions

## DELIVERY PROGRAM

Function  
I/O modules

Digital input modules

Function  
XNE Slice module

Short Description  
16 Digital inputs, 24 V DC  
Positive switching

## TECHNICAL DATA

### General

Standards  
EN 61000-6-2

EN61000-6-4  
EN61131-2

Potential isolation  
Yes, through optocoupler

Ambient temperature  
Ambient temperature, operation  
0 - +55 °C

Ambient temperature  
Storage, transport [9]  
-25 - +85 °C

Relative humidity  
Relative humidity  
5 - 95 % (indoor), Level RH+2, no condensation  
(for storage at 45°C)

Ambient conditions, mechanical  
Degree of Protection  
IP20

Ambient conditions, mechanical  
Harmful gases  
SO<sub>2</sub>: 10 (rel. humidity < 75%, no condensation)  
H<sub>2</sub>S: 1.0 (rel. humidity < 75%, no condensation)  
ppm

Vibration resistance, operating conditions  
according to IEC/EN 60068-2-6

Mechanical shock resistance  
according to IEC 60068-2-27 g

Continuous shock resistance (IEC/EN 60068-2-29)  
According to IEC 60068-2-29

Drop and topple  
According to IEC 60068-2-31, free fall according to  
IEC 60068-2-32

Electromagnetic compatibility (EMC)  
ESD [Air/contact discharge]  
EN 61000-4-2 kV

Electromagnetic compatibility (EMC)

Electromagnetic fields [(0.08...1) / (1,4...2) / (2...  
2,7) GHz ]  
EN 61100-4-2 V/m

Electromagnetic compatibility (EMC)  
Burst  
EN 61100-4-4

Electromagnetic compatibility (EMC)  
Surge  
EN 61100-4-5

Electromagnetic compatibility (EMC)  
Radiated RFI  
EN 61100-4-6 V

Electromagnetic compatibility (EMC)  
Emitted interference (radiated, high frequency)  
[(30...230 MHz) / (230...1000 MHz)]  
EN 55016-2-3 dB

Electromagnetic compatibility (EMC)  
Voltage fluctuations/voltage dips  
EN 61131-2

Electromagnetic compatibility (EMC)  
Type test  
to EN 61131-2

Approvals  
CE, cULus

Other technical data (sheet catalogue)  
Technical Data

## Terminations

Rated data  
according to VDE 0611 Part 1/8.92 /

IEC/EN 60947-7-1

Connection design in TOP direction  
Push-In spring-cage terminals

Stripping length  
8 mm

Clamping range  
max. 0.14 - 1.5 mm<sup>2</sup>

Connectable conductors  
"e" solid H07V-U  
0.25 - 1.5 mm<sup>2</sup>

Connectable conductors  
"f" flexible H07V-K  
0.25 - 1.5 mm<sup>2</sup>

Connectable conductors  
"f" with ferrules without plastic collar according to  
DIN 46228-1 (ferrules crimped gas-tight)  
0.25 - 1.5 mm<sup>2</sup>

Connectable conductors  
"f" with ferrules with plastic collar according to  
DIN 46228-1 (ferrules crimped gas-tight)  
0.25 - 0.75 mm<sup>2</sup>

Connectable conductors  
"e" solid H07V-U  
0.25 - 1.5 mm<sup>2</sup>

Connectable conductors  
"f" flexible H07V-K  
0.25 - 1.5 mm<sup>2</sup>

Connectable conductors  
"f" with ferrules without plastic collar according to  
DIN 46228-1 (ferrules crimped gas-tight)  
0.25 - 1.5 mm<sup>2</sup>

Connectable conductors  
"f" with ferrules with plastic collar according to  
DIN 46228-1 (ferrules crimped gas-tight)  
0.25 - 0.75 mm<sup>2</sup>

Gauge pin IEC/EN 60947-1  
A1

## Analog input modules

Channels  
16 Number

Rated voltage through supply terminal [U<sub>L</sub>]  
24 V DC

Rated current consumption from supply terminal [I<sub>L</sub>]  
3 mA

Rated current consumption from module bus [I<sub>MB</sub>]  
 15 mA

Heat dissipation  
< 2.5 W

Base modules  
without C connection  
Already built in

## Analog output modules

Channels  
16 Number

Rated voltage through supply terminal [U<sub>L</sub>]  
24 V DC

Rated current consumption from supply terminal [I<sub>L</sub>]  
3 mA

Rated current consumption from module bus [I<sub>MB</sub>]  
 15 mA

Heat dissipation  
< 2.5 W

Base modules  
without C connection  
Already built in

## Digital outputs

Channels  
16 Number

Rated voltage through supply terminal [ $U_L$  ]  
24 V DC

Rated current consumption from the supply  
terminal (at load current = 0 mA) [ $I_L$  ]  
3 mA

Rated current consumption from module bus [ $I_{MB}$  ]  
 15 mA

## Digital inputs

Channels  
16 Number

Rated voltage through supply terminal [ $U_L$  ]  
24 V DC

Rated current consumption from supply terminal [ $I_L$  ]  
3 mA

Rated current consumption from module bus [ $I_{MB}$  ]  
 15 mA

Rated insulation voltage [ $U$ ]  
500 V AC

Heat dissipation  
< 2.5 W

Input voltage  
Nominal input voltage [ $U_b$ ]  
24 V DC V DC

Input voltage  
Low level [ $U_{bL}$ ]  
 $-U_L$  - +5 V V

Input voltage  
High level [ $U_{bH}$ ]  
11 - 30 V V

Input current

Low level/active level [ $I_{eL}$ ]  
-1 mA - 1.5 mA mA

Input current  
High level/active level [ $I_{eH}$ ]  
2 mA - 5 mA mA

Input delay  
 $t_{\text{Rising edge}}$   
< 150  $\mu\text{s}$

Input delay  
 $t_{\text{Falling edge}}$   
< 300  $\mu\text{s}$

Base modules  
without C connection  
Already built in

## Relay modules

Rated voltage through supply terminal [ $U_L$ ]  
24 V DC

Rated current consumption from supply terminal [ $I_L$ ]  
3 mA

Rated current consumption from module bus [ $I_{MB}$ ]  
 15 mA

Base modules  
without C connection  
Already built in

## Power supply module

Rated voltage through supply terminal [ $U_L$ ]  
24 V DC

Rated current consumption from supply terminal [ $I_L$ ]  
3 mA

Rated current consumption from module bus [ $I_{MB}$ ]  
 15 mA

## Counter module

Channels  
16 Number

Rated voltage through supply terminal [ $U_L$ ]  
24 V DC

Rated current consumption from supply terminal [ $I_L$ ]  
3 mA

Rated current consumption from module bus [ $I_{MB}$ ]  
 15 mA

Heat dissipation  
< 2.5 W

## Digital inputs

Input voltage  
Nominal input voltage [ $U_e$ ]  
24 V DC V DC

Input voltage  
Low level [ $U_{eL}$ ]  
- $U_L$  - +5 V V

Input voltage  
High level [ $U_{eH}$ ]  
11 - 30 V V

Input current  
Low level [ $I_{eL}$ ]  
-1 mA - 1.5 mA mA

Input current  
High level [ $I_{eH}$ ]  
2 mA - 5 mA mA

## Interfaces

Rated voltage through supply terminal [ $U_L$ ]

24 V DC

Rated current consumption from supply terminal [ $I_L$ ]  
3 mA

Rated current consumption from module bus [ $I_{MB}$ ]  
□ 15 mA

### Notes

The supply terminal ( $U_L$ ) supplies power for the card's electronics and for the sensors at the inputs. The total current required for each card is the sum of all partial currents.

Part of the XI/ON card's electronics is supplied with module bus voltage (5 V DC), the other part through the supply terminal ( $U_L$ ).

Max. permissible capacity: 141 nF at 79 V AC/50 Hz; 23 nF at 265 V AC/50 Hz

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat dissipation [ $I_n$ ]  
0 A

Heat dissipation per pole, current-dependent [ $P_{id}$ ]  
0 W

Equipment heat dissipation, current-dependent [ $P_{id}$ ]  
0 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
2.5 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.

0 °C

Operating ambient temperature max.  
+55 °C

Degree of Protection  
IP20

### **IEC/EN 61439 design verification**

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Meets the product standard's requirements.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

PLCs (EG000024) / Fieldbus, decentr. periphery - digital I/O module (EC001599)

Electric engineering, automation, process control engineering / Control / Field bus, decentralized peripheral / Field bus, decentralized peripheral - digital I/O module (ecl@ss10.0.1-27-24-26-04 [BAA055014])

Supply voltage AC 50 Hz  
0 - 0 V

Supply voltage AC 60 Hz  
0 - 0 V

Supply voltage DC  
18 - 30 V

Voltage type of supply voltage  
DC

Number of digital inputs  
16

Number of digital outputs  
0

Digital inputs configurable  
No

Digital outputs configurable  
No

Input current at signal 1  
2 mA

Permitted voltage at input  
30 - 30 V

Type of voltage (input voltage)  
DC

Type of digital output  
None

Output current  
0 A

Permitted voltage at output  
0 - 0 V

Type of output voltage  
DC

Short-circuit protection, outputs available  
No

Number of HW-interfaces industrial Ethernet  
0

Number of interfaces PROFINET  
0

Number of HW-interfaces RS-232  
0

Number of HW-interfaces RS-422  
0

Number of HW-interfaces RS-485  
0

Number of HW-interfaces serial TTY  
0

Number of HW-interfaces parallel  
0

Number of HW-interfaces Wireless  
0

Number of HW-interfaces USB  
0

Number of HW-interfaces other  
1

With optical interface  
No

Supporting protocol for TCP/IP  
No

Supporting protocol for PROFIBUS  
Yes

Supporting protocol for CAN  
Yes

Supporting protocol for INTERBUS  
No

Supporting protocol for ASI  
No

Supporting protocol for KNX  
No

Supporting protocol for MODBUS  
No

Supporting protocol for Data-Highway  
No

Supporting protocol for DeviceNet  
No

Supporting protocol for SUCONET  
No

Supporting protocol for LON  
No

Supporting protocol for PROFINET IO  
No

Supporting protocol for PROFINET CBA  
No

Supporting protocol for SERCOS  
No

Supporting protocol for Foundation Fieldbus  
No

Supporting protocol for EtherNet/IP  
No

Supporting protocol for AS-Interface Safety at Work  
No

Supporting protocol for DeviceNet Safety  
No

Supporting protocol for INTERBUS-Safety  
No

Supporting protocol for PROFIsafe  
No

Supporting protocol for SafetyBUS p  
No

Supporting protocol for other bus systems  
Yes

Radio standard Bluetooth  
No

Radio standard WLAN 802.11  
No

Radio standard GPRS  
No

Radio standard GSM  
No

Radio standard UMTS

No

IO link master

No

System accessory

Yes

Degree of protection (IP)

IP20

Type of electric connection

Screw-/spring clamp connection

Time delay at signal exchange

0 - 0 ms

Fieldbus connection over separate bus coupler

possible

Yes

Rail mounting possible

Yes

Wall mounting/direct mounting

No

Front build in possible

No

Rack-assembly possible

No

Suitable for safety functions

No

Category according to EN 954-1

None

SIL according to IEC 61508

None

Performance level acc. EN ISO 13849-1

None

Appendant operation agent (Ex ia)  
No

Appendant operation agent (Ex ib)  
No

Explosion safety category for gas  
None

Explosion safety category for dust  
None

Width  
13 mm

Height  
161.5 mm

Depth  
74.5 mm

## APPROVALS

Product Standards  
UL 508; CSA-C22.2 No. 142; IEC/EN 6113-2; CE  
marking

UL File No.  
E205091

UL Category Control No.  
NRAQ, NRAQ7

CSA File No.  
UL report applies to both US and Canada

CSA Class No.  
2252-01, 2252-81


North America Certification  
UL recognized, certified by UL for use in Canada  
17 / 19

Specially designed for North America  
No

Current Limiting Circuit-Breaker  
No

Degree of Protection  
IEC: IP20, UL/CSA Type: -

## DIMENSIONS



[Link to sheet catalogue](#)  
Dimensions



