



Connecting cable for networking devices via easyNet, 2xRJ45, 80cm



Powering Business Worldwide™

Part no. **EASY-NT-80**
Article no. **256284**

Delivery program

| | | |
|--------------|---|--|
| Description | | Connection cable for XC200 to interface switch |
| Length | m | 0.8 |
| For use with | | easy800 MFD-...-CP8... |
| For use with | | easyNet |

Technical data

Pairs 2 x 0.14 mm²

| | | |
|--------------------|-----------------|---|
| Conductor material | | E-Cu 58 F21 nach DIN 40500 Teil 4 |
| Conductor material | | Max. 0.49 mm (Cu wire bare 7 x 0.16 mm ²) |
| Core | | 0.60 mm ±0.10 (dielectric polyethylene, halogen free, every two cores paired and twisted: wsbl-bl, wsor-or, wsgn-gn, wsbr-br) |
| Stranding | | Four pairs |
| Sheath | mm ² | 4.5 mm ± 0.2 (halogen free casing material, flame retardant (FRNC)) |

Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|--|-------------------|----|--|
| Rated operational current for specified heat dissipation | I _n | A | 0 |
| Heat dissipation per pole, current-dependent | P _{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P _{vs} | W | 0 |
| Heat dissipation capacity | P _{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 55 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3 Verification of thermal stability of enclosures | | | |
| 10.2.3.1 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Meets the product standard's requirements. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. |

| | | |
|---------------------------|--|--|
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
|---------------------------|--|--|

Technical data ETIM 6.0

| | | |
|--|-----------------|--------------------------|
| Cables and wires unpreassembled (EG000001) / Data cable (EC000830) | | |
| Electric engineering, automation, process control engineering / Cable, wire / Communication cable / Data cable (ecl@ss8.1-27-06-18-01 [AKE197011]) | | |
| Conductor material | | Cu, bare |
| Diameter conductor | mm | 4.5 |
| Nominal cross section conductor | mm ² | 0.14 |
| AWG-size | | 26 |
| Conductor category | | Class 2 = stranded |
| Number of cores | | 8 |
| Stranding element | | Pairs |
| Core insulation | | Copolymer, thermoplastic |
| Core identification | | Colour |
| Screen over stranding element | | None |
| Screen over stranding | | None |
| Material outer sheath | | PVC |
| Colour outer sheath | | Grey |
| Halogen free (acc. EN 60754-1/2) | | Yes |
| Flame retardant | | No |
| Low smoke (acc. EN 61034-2) | | Yes |
| Outer diameter approx. | mm | 4.5 |
| Permitted cable outer temperature, in movement | °C | -25 - 60 |
| Permitted cable outer temperature, fixed | °C | -25 - 60 |
| Category | | 5E |
| NVP value | % | 67 |

Approvals

| | | |
|-----------------------------|--|---|
| Product Standards | | IEC/EN see Technical Data; UL 508; CSA C22.2 No. 142-M1987; CSA C22.2 No. 213-M1987; CE marking |
| UL File No. | | E135462 |
| UL Category Control No. | | NRAQ |
| CSA File No. | | 012528 |
| CSA Class No. | | 2258-02 |
| North America Certification | | UL listed, CSA certified |
| Degree of Protection | | IEC: IP20, UL/CSA Type: - |

Additional product information (links)

| | |
|---|---|
| Manual "easy800 control relays" MN04902001Z (AWB2528-1423) | |
| MN04902001Z (AWB2528-1423) Steuerrelais easy800 - Deutsch | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04902001Z_DE.pdf |
| MN04902001Z (AWB2528-1423) easy800 control relay - English | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04902001Z_EN.pdf |
| Manual "easy500, easy700 control relays" MN05013003Z (AWB2528-1508) | |
| MN05002001Z (AWB2528-1480) Multi-Funktions-Display MFD-Titan - Deutsch | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05013003Z_DE.pdf |
| MN05002001Z (AWB2528-1480) MFD-Titan multi-function display - English | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05013003Z_EN.pdf |
| MN05002001Z (AWB2528-1480) Multi-Funktions-Display MFD-Titan - Deutsch | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05002001Z_DE.pdf |
| MN05002001Z (AWB2528-1480) MFD-Titan multi-function display - English | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05002001Z_EN.pdf |
| Manual "easyControl, EC4-200 programmable PLC" MN05003003Z | |
| MN05003003Z Handbuch easyControl, Programmierbare Steuerung EC4-200 - Deutsch | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05003003Z_DE.pdf |
| MN05003003Z Manual easyControl, programmable PLC EC4-200 - English | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05003003Z_EN.pdf |

