

**Wireless xComfort Bridge package, flush mount, 3 Smart Dimming Actuators, 0-100W, 230VAC, R/L/C/LED, 3 wireless switches, 1 wireless master switch, Pure white gloss**



**Part no.** CPAD-00/221  
**Catalog No.** 300310

## Delivery program

|                          |  |  |                                          |
|--------------------------|--|--|------------------------------------------|
| Product Type             |  |  | Packaged Units<br>Actuator<br>Pushbutton |
| Mounting type            |  |  | Flush mounted<br>Surface mounted         |
| Power supply             |  |  | Battery<br>Mains                         |
| Actuation Function       |  |  | Dimming                                  |
| Pushbutton compatibility |  |  | 55 mm (Universal)                        |
| Rocker Pitch             |  |  | 1-gang                                   |
| Color                    |  |  | Pure White                               |

## Technical data ETIM 7.0

|                                                                                                                                                                                   |  |    |                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|----------------------------|
| Installation bus systems (EG000032) / Dimming actuator for bus system (EC001094)                                                                                                  |  |    |                            |
| Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Bus system dimming actuator (ecl@ss10.0.1-27-14-31-23 [AKE291015]) |  |    |                            |
| Bus system KNX                                                                                                                                                                    |  |    | No                         |
| Bus system KNX radio                                                                                                                                                              |  |    | No                         |
| Bus system radio frequent                                                                                                                                                         |  |    | Yes                        |
| Bus system LON                                                                                                                                                                    |  |    | No                         |
| Bus system Powernet                                                                                                                                                               |  |    | No                         |
| Other bus systems                                                                                                                                                                 |  |    | xComfort                   |
| Radio frequent bidirectional                                                                                                                                                      |  |    | Yes                        |
| Model                                                                                                                                                                             |  |    | Dimming actuator           |
| Mounting method                                                                                                                                                                   |  |    | Flush mounted (plaster)    |
| Width in number of modular spacings                                                                                                                                               |  |    | 3                          |
| Bus connection included                                                                                                                                                           |  |    | Yes                        |
| Bus module detachable                                                                                                                                                             |  |    | No                         |
| Substation input                                                                                                                                                                  |  |    | No                         |
| Local operation/hand operation                                                                                                                                                    |  |    | No                         |
| With LED indication                                                                                                                                                               |  |    | Yes                        |
| Number of outputs                                                                                                                                                                 |  |    | 1                          |
| Output power                                                                                                                                                                      |  | W  | 0 - 100                    |
| Power boost suitable                                                                                                                                                              |  |    | No                         |
| Type of load                                                                                                                                                                      |  |    | Universal and LED Retrofit |
| Max. control current                                                                                                                                                              |  | mA | 0                          |
| Voltage                                                                                                                                                                           |  | V  | 196 - 253                  |
| Parallel-service possible                                                                                                                                                         |  |    | No                         |
| Frequency                                                                                                                                                                         |  | Hz | 50 - 50                    |
| Degree of protection (IP)                                                                                                                                                         |  |    | IP20                       |
| Min. depth of built-in installation box                                                                                                                                           |  | mm | 18                         |