

Features

- Ultra low current consumption
- RoLP and RoLP Maxi sounder options
- Up to 7.5m coverage volume (switchable to 2.5m)
- 0.5 or 1Hz flash rate •

Benefits

- Use where current consumption is a key consideration
- Delivering up to 106dB(A) sound output
- Ideal for bedrooms, bathrooms and toilets
- Switch flash rate to 0.5Hz to reduce current consumption ٠

Dimensions





RoLP LX Wall White



RoLP Base White





Catalogue Numbers

| Reference | Cat No | Description |
|------------------|-------------------|---|
| ROLP/W1/LX-W/RF | 8500024FULL-0024X | RoLP LX Wall, Red Flash, White Body |
| ROLP/R1/LX-W/RF | 8500025FULL-0025X | RoLP LX Wall, Red Flash, Red Body |
| ROLP/R1/LX-W/WF | 8500023FULL-0023X | RoLP LX Wall, White Flash, Red Body |
| ROLPX/W1/LX-W/RF | 8500029FULL-0029X | RoLP Maxi LX Wall, Red Flash, White Body |
| ROLPX/R1/LX-W/RF | 8500030FULL-0030X | RoLP Maxi LX Wall, Red Flash, Red Body |
| ROLPX/R1/LX-W/WF | 8500028FULL-0028X | RoLP Maxi, LX Wall, White Flash, Red Body |

For full list of part numbers, turn to page 80



Based on the popular Roshni product platform, the RoLP LX is a reliable, high performing VAD (Visual

to an audible alarm.

Recommended for wall use and requiring just one installation point, the RoLP LX Wall is also available as a base only for use with any standard RoLP sounder, including the high output RoLP Maxi sounder.

Alarm Device) that is certified to EN 54-23.

The RoLP LX Wall is ideal for dual use applications where a visual alarm device is required in addition

Technical Specification

| Mounting | Wall |
|-----------------------|---|
| Voltage | 18 - 28VDC (Fire Use) 9 - 15 VDC (Fire Use) |
| Current | 22 - 37mA dependent on setting (Sounder and beacon; tone 3) |
| Coverage (y) | 7.5m (Switchable to 2.5m)* |
| Mounting Height (x) | 2.4m (max) |
| Coverage Volume Code | W-2.4-7.5 |
| Coverage Volume | 135m³ (15m³) |
| Flash Rate | 1Hz (Switchable to 0.5Hz) |
| Operating Temperature | -25°C to +70°C |
| Monitoring | Reverse Polarity |
| Protection | IP65 |
| Weight | 200g |
| Body Colour | White or Red |
| Flash Colour | White or Red |
| Sound Output | 102dB(A) (Typical tone 3 - RoLP) |
| * CNPP test results | |
| | |

FULLEON FIRE ALARM DEVICES CAFIRV10614