The Solista Maxi, a LED beacon which gives the choice between economy and performance. In the economy mode the Solista Maxi performs extremely efficiently requiring as little as 3mA. But it can be switched to attain much higher light output where visibility is the prime objective. For even greater effectiveness a double flash sequence can be selected.

CE

Technical Specification

Voltage	9 - 60Vdc (*1)
Current	3 / 5 / 15mA (user selectable)
Light Output	0.5 / 1 / 3cd (user selectable)
Flash Rate	Single flash @ 1Hz Double flash @ 1Hz Continuous (user selectable)
Monitoring	Reverse polarity
Temperature	- 10ºC to + 55ºC
Protection	IP21C (s)* IP65 (d)*
Construction	Base ABS, FR, PC lens
Weight	0.1Kg
Colour	Red or white
Flash colour	Red, amber, blue, green or white

(*1) 110 / 230Vac when used with a Deep powered base.

(s)* Shallow Base

(d)* Deep / U Base

Features

Catalogue No.

811021FULL-0037

811020FULL-0036

811041FULL-0006

811023FULL-0039

811024FULL-0040

811057FULL-0082

- Ultra low current consumption
- LED technology
- Long service life
- Compact size

Reference

SOLX/RF/RL/R/S SOLX/RF/RL/R/D SOLX/RF/CL/R/S SOLX/RF/CL/W/S SOLX/RF/RL/W/D SOLX/AF/CL/R/D + MAINS MODULE

Benefits

- Use where current consumption is a key consideration
- Ensures high efficiency and long life
- Reduces maintenance costs
- Discrete option where aesthetics or space is a priority

Description

Solista Maxi, Red Body, Red Flash, Shallow Base, Red Lens Solista Maxi, Red Body, Red Flash, Deep Base, Red Lens Solista Maxi, Red Body, Red Flash, Clear Lens Solista Maxi, White Body, Red Flash, Shallow Base, Clear Lens Solista Maxi, White Body, Red Flash, Deep Base, Clear Lens Solista Maxi, Red Body, Amber Flash, Clear Lens, Deep Base + Mains Mod





